

Nuova Distribution USA, LLC

6940 Salashan Parkway, Building A • Ferndale, WA 98248 www.nuovadistribution.com • (p) 360-366-2226 • (f) 360-366-4015

Appia II Compact 220V 2 Group Spec Sheet

Water Requirements

- 3/8" dedicated cold water line with shut-off valve and compression fitting.
- Water hardness cannot exceed 3gpg or 50 ppm. If water hardness exceeds 3gpg a water softener must be installed.
- Minimum incoming water flow rate of 35 GPH and maximum line pressure of 70 PSI / 5 BAR.

Water Softening Equipment

- 1. Water Softener Capacity: Single 4400 gpg
- 2. Water Softener Capacity: Double 8800 gpg
- 3. Water Softener Capacity: Triple 13200 gpg
- 4. Water Softener Capacity: Automatic Programmable
- 5. Water Softener Capacity: Manual 4400 gpg

Power Requirements

• Volts: 220 (voltage range of 208-240)

Watts: 3000Amp draw: 14

Receptacle: Nema 6-20









NSF / ANSI Std.4

The average water consumption of this machine is 4 gallons per day, which represents 128 drinks at 4oz per drink.

Water Softener/Maintenance Calculation

Cartridge Grain
Capacity

Water Hardness
(grains per gallon)

Gallon Capacity
of Cartridge

Gallons of Water
Used per Day

Days Until Cartridge
Needs to be Replaced

Shipping Dimensions & Weight


Height: 27 inchesDepth: 24 inchesWidth: 24 inchesWeight: 150 pounds

Counter Space Requirements

Height: 21 inchesDepth: 22 inchesWidth: 22 inchesWeight: 130 pounds

Drain Requirements

 Open gravity drain of minimum 1.25 inch I.D., within 4 feet of the machine.





| I, the customer, understand that these requirements must be in when the installer arrives. Failure to have the site ready will result in additional service and travel charges, and may cause further delays in installation. | | |
|---|--------------|--------|
| Customer Name: | Signature: _ | |
| Company Name: | | |
| Phone: | Fax: | Email: |